

TYPE 304 #4			STAINLESS STEEL SHEET					
			Specification: ASTM A240, SA 240, A 480					
GA.	Thickness Inches	Lbs. Per Sq. Ft.	STANDARD SHEET SIZES Fiber Laser & CO ₂ Laser PVC Protection, one side.					
24	.024"	1.008	48 x 96	48 x 120				
22	.030"	1.260	48 x 96	48 x 120				
20	.036"	1.512	48 x 96	48 x 120	48 x 144	60 x 120	60 x 144	
18	.048"	2.016	48 x 96	48 x 120	48 x 144	60 x 120	60 x 144	
16	.060"	2.520	48 x 96	48 x 120	48 x 144	60 x 120	60 x 144	
14	.075"	3.150	48 x 96	48 x 120	48 x 144	60 x 120	60 x 144	
12	.105"	4.411	48 x 96	48 x 120	48 x 144	60 x 120	60 x 144	
11	.120"	5.041	48 x 96	48 x 120				
10	.135"	5.671	48 x 96	48 x 120	48 x 144	60 x 120	60 x 144	

TYPE 304 2B			STAINLESS STEEL SHEET					
			Specification: ASTM A240, SA 240, A 480					
GA.	Thickness Inches	Lbs. Per Sq. Ft.	STANDARD SHEET SIZES					
26	.018"	0.756	48 x 120					
24	.024"	1.008	48 x 96	48 x 120				
22	.030"	1.260	48 x 96	48 x 120				
20	.036"	1.512	48 x 96	48 x 120	48 x 144	60 x 120		
18	.048"	2.016	48 x 96	48 x 120	48 x 144	60 x 96	60 x 120	60 x 144
16	.062"	2.520	48 x 96	48 x 120	48 x 144	60 x 96	60 x 120	60 x 144
14	.075"	3.150	48 x 96	48 x 120	48 x 144	60 x 96	60 x 120	60 x 144
12	.105"	4.411	48 x 96	48 x 120	48 x 144	60 x 96	60 x 120	60 x 144
11	.125"	5.041	48 x 96	48 x 120	60 x 120			
10	.135"	5.671	48 x 96	48 x 120	48 x 144	60 x 120	60 x 144	

TYPE 304L HRAP			STAINLESS STEEL PLATE					
			AISI 304/304L #1 Finish. HOT ROLLED, ANNEALED AND PICKLED Specification: ASTM A240, SA 240, A 480					
	Thickness Inches	Lbs. Per Sq. Ft.	STANDARD PLATE SIZES					
3/16	.188"	8.579	48 x 96	48 x 120	48 x 144	60 x 120	60 x 144	
1/4	.250"	11.160	48 x 96	48 x 120	48 x 144	60 x 120	60 x 144	
3/8	.375"	16.496	48 x 96	48 x 120	60 x 120			
1/2	.500"	21.665	48 x 96	48 x 120	60 x 120			