

GRADE 5052-H32			ALUMINUM SHEET					
			Specification: ASTM B209, AMS QQA-250/8					
GA.	Thickness Inches	Lbs. Per Sq. Ft.	STANDARD SHEET SIZES					
22	.025"	0.355	48 x 96	48 x 120				
20	.030"	0.455	48 x 96	48 x 120	60 x 120			
18	.040"	0.569	48 x 96	48 x 120				
16	.050"	0.711	48 x 96	48 x 120	48 x 144	60 x 120		
14	.063"	0.895	48 x 96	48 x 120	48 x 144	60 x 120	60 x 144	
12	.080"	1.137	48 x 96	48 x 120	60 x 96	60 x 120		
11	.090"	1.279	48 x 96	48 x 120				
10	.100"	1.421	36 x 96	36 x 120	48 x 96	48 x 120	60 x 120	60 x 144
1/8	.125"	1.777	48 x 96	48 x 120	48 x 144	60 x 96	60 x 120	60 x 144
5/32	.156"	1.421	48 x 96	48 x 120	60 x 120			
3/16	.188"	2.665	48 x 96	48 x 120	48 x 144	60 x 96	60 x 120	60 x 144
1/4	.250"	3.553	48 x 96	48 x 120	48 x 144	60 x 96	60 x 120	60 x 144
3/8	.375"	5.330	48 x 96	48 x 120				
1/2	.500"	7.106	48 x 96	48 x 120	60 x 120			

GRADE 3003-H22			ALUMINUM TREAD PLATE					
			Diamond Pattern Specification: ASTM B209, AMS QQA-250/2					
GA.	Thickness Inches	Lbs. Per Sq. Ft.	STANDARD SHEET SIZES					
14	.063"	1.010	48 x 96	48 x 120	60 x 120			
1/8	.125"	1.919	48 x 96	48 x 120	48 x 192	60 x 120	60 x 144	60 x 192
3/16	.188"	2.818	48 x 96	48 x 120	48 x 144	48 x 192	60 x 120	Cont.
3/16	.188"	2.818	60 x 144	60 x 192				
1/4	.250"	3.707	48 x 96	48 x 120	60 x 120	60 x 144	60 x 192	